SATCO" NUVO"

Project Name

Location

Prepared By



NUVO 65-845-5

200W LED AREA LIGHT TYPE V

Notes

www] 01-15-2024 02:40:07

ixture TypeArea LightFinishBronzeWattage200WLumen Output26536LCCT (Kelvin)5000KFemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecifications80Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DinmableYes-DinmableOptional-10V DimmingPhotocell or SensorOptionalPhotocell or SensorOptionalPolycarbonate (PC)Surge Protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions	General	
Fixture TypeArea LightFinishBronzeWattage200WLumen Output26536LCGT (Kelvin)5000KFemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecifications80Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DinmableYes-DinmableDinming Note0-10V DimmingPhotocell or SensorOptional_ens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42VaterialDie-cast AluminumDimensions22.4ComplianceSurgeSafety ListingcULus - Certified_ocation RatingWetEnergy StarNoDLC ApprovedYesDuC IDS-HR2WBXJ.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaCalifornia InformationYeesCC CompliantYeesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	Status	Active
FinishBronzeMattage200WLumen Output26536LCCT (Kelvin)5000KTemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecifications120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note-10V DimmingPhotocell or SensorOptionalPertorectionBuilt-in surge protection - 4KVWeight (lb.)8.42VaterialDie-cast AluminumDimensions22.4ComplianceVelsSafety ListingcULus - CertifiedLocation RatingWetBenry StarNoOLC ApprovedYesDUC ApprovedYesDLC IDS-HR2WBXJ.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia StatusLeadCalifornia StatusLeadCalifornia In App 65LeadCompliantYesCC CompliantYesCC Compliant <td></td> <td></td>		
Internet26536LCCT (Kelvin)5000KTemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDCRI80Voltage120V-277VRated Hours50000Operating Temperature-40C (40F) to +45C (+113F)DimmableYes-DimmableOptional-ens MaterialPoltocell or SensorOptionalCongenetications0000Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42VaterialDie-cast AluminumDimensions22.4Compliance22.4ComplianceVesSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in California Title 20 / 24 StatusCalifornia StatusLawful for saleCalifornia Prop 65LeadCompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ruledsColubiantPowder CoatedSpecification NoteType V Light DistributionCompliantCoated	Finish	
Lumen Output26536LCCT (Kelvin)5000KTemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (40F) to +45C (+113F)Dimmable0-10V DimmingOptional0-10V DimmingPhotocell or SensorOptionalPolycarbonate (PC)8.42Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42MaterialDie-cast AluminumDimensions22.4ComplianceSafety ListingCulus - CertifiedLocation RatingWetEnergy StarNoCL ApprovedYesDuc IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in California Title 20 / 24 StatusCalifornia Prop 65LeadCalifornia Prop 65LeadCalifornia InformationYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ruedncludes2-3/8 inch Slip-fitter Mount	Wattage	200W
CCT (Kelvin)5000KTemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor: OutdoorSpecificationsEEDState of Construct on Some of Construct on	Lumen Output	26536L
FemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsIEDSpecifications80Voltage120V-277VRated Hours50000Operating Temperature40C (40F) to +45C (+113F)DimmableYes-DimmableDimmable0-10V DimmingPhotocell or SensorOptionalDimensions0perating TemperaturePhotocell or SensorOptionalDimensionsBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions14.4Length (in.)3.11Width (in.)14.4Length (in.)3.11Midth (in.)14.4Length (in.)5.4R2WBXSafety ListingcULus - CertifiedJocation RatingWetSurge StarNoDLC ApprovedYesDLC JDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleRegulatedRegulatedCaliforniaCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalifornia Prop 65LeadCA CompliantYesCC CompliantYesCDC CompliantYesCC CompliantYesCDC CompliantYesCDC CompliantYesCDC CompliantYesSDS SheetLED_FixtureAddit	CCT (Kelvin)	5000K
Indeor or Outdoor FixtureIndeor; OutdoorSpecificationsIndeor; OutdoorSpecificationsIndeor; OutdoorSpecifications80CRI80Voltage120V-277VRated Hours50000Deparating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KNWeight (ib.)8.42MaterialDie-cast AluminumDimensions14.4Length (in.)14.4Length (in.)22.4ComplianceSafety ListingCulc ApprovedYesDLC ApprovedYesDLC ApprovedYesDLC ApprovedS-HR2WBXBJ.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadCompliantYesCC CompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution a-3/8 inch Slip-fitter Mount	Temperature	Natural Light
SpecificationsSpecificationsFechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (+40F) to +45C (+113F)VimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalPens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions14.4Length (in.)14.4Length (in.)22.4ComplianceVetSafety ListingCULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoth S CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributioncalifonia Status2a/8 inch Slip-fitter Mount	IP Rating	IP65
TechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (-40F) to +45C (+113F)Ves-DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptional_ens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KNWeight (lb.)8.42WaterialDie-cast AluminumDimensions2.4Veight (in.)3.11Width (in.)14.4_ength (in.)2.4ComplianceWetSafety ListingcULus - Certified_ocation RatingWetDuC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoth ScompliantYesCC CompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	Indoor or Outdoor Fixture	Indoor; Outdoor
TechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (-40F) to +45C (+113F)Ves-DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptional_ens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KNWeight (lb.)8.42WaterialDie-cast AluminumDimensions2.4Veight (in.)3.11Width (in.)14.4_ength (in.)2.4ComplianceWetSafety ListingcULus - Certified_ocation RatingWetDuC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoth ScompliantYesCC CompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	Specifications	
CRIBitCRI80Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalPhotocell or SensorOptionalBuilt-in surge protectionBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions14.4-teight (in.)3.11Midth (in.)14.4energth (in.)22.4ComplianceVesSafety ListingCULus - CertifiedLocation RatingWetDLC ApprovedYesDL C IDS-HR2WBX3.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadCA CompliantYesCC CompliantYesCD SheetLED_FixtureAdditional InformationPowder CoatedSpec		
Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KNWeight (lb.)8.42VaterialDie-cast AluminumDimensions3.11Midth (in.)14.4_ength (in.)3.11Midth (in.)14.4_ength (in.)22.4ComplianceVetSafety ListingcULus - Certifiedocation RatingWetEnergy StarNoDLC ApprovedYesDCC IDS-HR2WBXBJ.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributioncludes2-3/8 inch Silp-fitter Mount		
Rated Hours50000Operating Temperature40C (40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions3.11Height (in.)3.11Midth (in.)14.4Length (in.)22.4ComplianceWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXBJUG. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadCompliantYesSD SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributioncludes2-3/8 inch Silp-fitter Mount		
Deperating Temperature40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptional_ens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KNWeight (lb.)8.42WaterialDie-cast AluminumDimensions14.4_ength (in.)3.11Width (in.)14.4_ength (in.)22.4ComplianceWetSafety ListingCULus - Certified_ocation RatingWetDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Silp-fitter Mount	•	
DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions3.11Height (in.)3.11Midth (in.)14.4Length (in.)22.4ComplianceWetSafety ListingcULus - CertifiedLocation RatingWetDuc ApprovedYesDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in California Title 20 / 24 StatusCalifornia Prop 65LeadCompliantYesCC CompliantYesCC CompliantYesCD SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionAdditional InformationPowder Coated		
Dimming Dimming NoteDistributionDimming Note0-10V DimmingPhotocell or SensorOptional_ens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KNWeight (lb.)8.42MaterialDie-cast AluminumDimensions14.4-ength (in.)3.11Midth (in.)14.4_ength (in.)22.4ComplianceWetSafety ListingcULus - Certified_ocation RatingWetDic ApprovedYesDLC IDS-HR2WBXBJ.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesCC CompliantYesCC CompliantYesCC CompliantYesCD / 24 StatusLawful for sale in CaliforniaCalifornia InformationYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount		
Photocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42MaterialDie-cast AluminumDimensions14.4Length (in.)14.4Length (in.)22.4ComplianceVetSafety ListingcULus - CertifiedLocation RatingWetDirengy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLeavful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaCalifornia StatusLeadCalifornia StatusLeadCompliantYesCC CompliantYesCSD SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount		
Lens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42MaterialDie-cast AluminumDimensions14.4-ength (in.)3.11Midth (in.)14.4-ength (in.)22.4ComplianceULus - CertifiedSafety ListingCULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in California Lawful for saleCalifornia Prop 65LeadCA GC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder Coated Type V Light Distribution a.culdesCalifornia InformationPowder Coated	Photocell or Sensor	
Surge ProtectionBuilt-in surge protection - 4KNWeight (lb.)8.42MaterialDie-cast AluminumDimensions14.4Leight (in.)3.11Width (in.)14.4Length (in.)22.4ComplianceULus - CertifiedSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXBJ.UG. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution z-3/8 inch Slip-fitter Mount	Lens Material	· · ·
Weight (lb.)8.42WaterialDie-cast AluminumDimensions3.11Height (in.)14.4Length (in.)14.4Length (in.)22.4Compliance22.4Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXBJUG. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification Note2-3/8 inch Slip-fitter Mount		
MaterialDie-cast AluminumDimensionsHeight (in.)3.11Midth (in.)14.4Length (in.)22.4ComplianceSafety ListingcULus - CertifiedLocation RatingWetLocation RatingVetDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ancludesAdditional StatusSuch Slip-fitter Mount	Weight (lb.)	
DimensionsHeight (in.)3.11Width (in.)14.4Length (in.)22.4ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ancludesAdditional Status2-3/8 inch Slip-fitter Mount	Material	
Height (in.)3.11Width (in.)14.4Length (in.)22.4Compliance22.4Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution a.748 inch Slip-fitter Mount		
Width (in.)14.4Length (in.)22.4ComplianceSafety ListingcULus - CertifiedLocation RatingWetLocation RatingVetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXBJ.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution rulesncludes2-3/8 inch Slip-fitter Mount	Dimensions	
Length (in.)22.4ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution rupe V Light Distributionncludes2-3/8 inch Slip-fitter Mount	Height (in.)	3.11
ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ac-3/8 inch Slip-fitter Mount	Width (in.)	14.4
Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ancludesAddito ScienceSinch Slip-fitter Mount	Length (in.)	22.4
Location RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalor CompliantYesCC CompliantYesCD CompliantYesCalifornia Prop 65LeadRoHS CompliantYesCD CompliantYesCompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ancludesCalifornia StatusSinch Slip-fitter Mount	Compliance	
Location RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution a.3/8 inch Slip-fitter Mount	Safety Listing	cULus - Certified
Energy StarNoDLC ApprovedYesDLC IDS-HR2WBXB.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalornia Prop 65LeadCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ac-3/8 inch Slip-fitter Mount	Location Rating	Wet
DLC IDS-HR2WBX3.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ncludes2-3/8 inch Slip-fitter Mount	Energy Star	No
B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalifornia Prop 65LeadFCC CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution 2-3/8 inch Slip-fitter Mount	DLC Approved	Yes
Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distribution ncludes2-3/8 inch Slip-fitter Mount	DLC ID	S-HR2WBX
CA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	B.U.G. Rating	B5-U3-G2
CA 120 / 124 RationaleRegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	Dark Sky Compliant	No
Title 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	CA T20 / T24 Rationale	•
California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Powder Coated Specification Note Type V Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	California Status	Lawful for sale in California
RoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	Title 20 / 24 Status	Lawful for sale
FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Additional Information Additional Information Powder Coated Specification Note Type V Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	California Prop 65	Lead
SDS SheetLED_FixtureAdditional InformationPowder CoatedAdditional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	RoHS Compliant	Yes
Additional Information Additional Information Powder Coated Specification Note Type V Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	FCC Compliant	Yes
Additional InformationPowder CoatedSpecification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	SDS Sheet	LED_Fixture
Specification NoteType V Light Distributionncludes2-3/8 inch Slip-fitter Mount	Additional Information	
ncludes 2-3/8 inch Slip-fitter Mount	Additional Information	Powder Coated
· · · · · ·	Specification Note	Type V Light Distribution
Warranty 5 Year Limited - Fixtures	Includes	2-3/8 inch Slip-fitter Mount
	Warranty	5 Year Limited - Fixtures

