## SATCO" NUVO"

Project Name

Location

Prepared By



## NUVO 65-848-5

300W LED AREA LIGHT TYPE V

Notes

wwwj 01-15-2024 02:40:07

StatusActiveFixture TypeArea LightFinishBronzeWattage300WLumen Output39815LCCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecifications200%TechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (-40F) to +45C (+113F)Dimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensions201Lecation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. Rating55-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	General	
Fixture TypeArea LightFinishBronzeWattage300WLumen Output39815LCCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (40F) to +45C (+113F)Dimming Note0-10V DimmingPhotocell or SensorOptionalDimening Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (ib.)12.35MaterialDie-cast AluminumDimensions239Length (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceVetSafety ListingcULus - CertifiedLocation RatingWetDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures NotRegulatedCaliforniaCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-		Active
FinishBronzeWattage300WLumen Output39815LCCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (40F) to +45C (+113F)DimmableYes-DimmablePhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (In.)12.35MaterialDie-cast AluminumDimensions12.39Length (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceYesSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDL C ApprovedYesDL C ApprovedYesDL A StatusLawful for sale in CaliforniaUA: Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadRoditional InformationYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
Wattage300WLumen Output39815LCCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureIndoor, OutdoorSpecifications80CRI80Voltage120V-277VRated Hours50000Operating Temperature40C (40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensions12.39Length (in.)3.11Width (in.)12.39Length (in.)SelectionSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDL ApprovedYesDL ApprovedT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesCC CompliantYesCC CompliantYesCC CompliantYesCC CompliantYesCD CompliantYesCD CompliantYesCD CompliantYesCD CompliantYesCD CompliantYesCD CompliantYesCD Com		
Lumen Output39815LCCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (40F) to ±45C (±113F)DinmableYes-DinmableDinming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensionsJuneLocation RatingWetSafety ListingcULus - CertifiedLocation RatingWetBul.C. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia StatusLeadCalifornia InformationYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	-	
CCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDTechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensions2028Compliance2028Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia FatusYesSDS SheetYesCA CompliantYesCA CompliantYesCA CompliantYesCA CompliantYesCA CompliantYesCalifornia ItormationPowder CoatedSp SheetLeD_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes		39815L
TemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDTechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DinmableYes-DinmableDinming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensionsJillWidth (in.)3.11Width (in.)30.28ComplianceVesSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		4000K
IP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsIndoor; OutdoorSpecificationsEEDCRI80Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DinmableYes-DinmableDinming Note0-10V DimmingPhotocell or SensorOpionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensions3.11Width (in.)12.39Length (in.)3.12Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	, ,	Cool White
SpecificationsTechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensions30.28ComplianceVetSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleI20 Exempt - Fixtures Not RegulatedCalifornia StatusLeadul for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	IP Rating	IP65
TechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuill-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensions12.39Height (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceWetSafety ListingCULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLeadCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	3	Indoor; Outdoor
CRI80CRI80Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (b.)12.35MaterialDie-cast AluminumDimensions12.39Length (in.)3.11Wdth (in.)12.39Length (in.)30.28ComplianceSafety ListingSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Specifications	
CRI80Voltage120V-277VRated Hours50000Operating Temperature40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (b.)12.35MaterialDie-cast AluminumDimensions12.39Length (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceWetSafety ListingCULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Technology	LED
Rated Hours50000Qperating Temperature40C (40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensionsJinensionsHeight (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingCullus - CertifiedLocation RatingWetEnergy StarNoDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionLocudes2-3/8 inch Slip-fitter Mount	CRI	80
Rated Hours50000Qperating Temperature40C (40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensionsJinensionsHeight (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingCullus - CertifiedLocation RatingWetEnergy StarNoDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionLocudes2-3/8 inch Slip-fitter Mount		
Operating Temperature40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensions3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Silp-fitter Mount	-	
DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensionsHeight (in.)Safety Listing3.11Location RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionLicudes2-3/8 inch Silp-fitter Mount		-40C (-40F) to +45C (+113F)
Dimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensionsHeight (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleLeavful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fiiter Mount	Dimmable	
Photocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensionsHeight (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fiiter Mount	Dimming Note	0-10V Dimming
Lens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensionsHeight (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLeavful for sale in CaliforniaTitle 20 / 24 StatusLeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)12.35MaterialDie-cast AluminumDimensions3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Lens Material	· ·
Weight (lb.)12.35MaterialDie-cast AluminumDimensions3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Surge Protection	,
DimensionsHeight (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Weight (lb.)	
Height (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Material	Die-cast Aluminum
Height (in.)3.11Width (in.)12.39Length (in.)30.28ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Dimensions	
Width (in.)12.39Length (in.)30.28ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		3 11
Length (in.)30.28ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Length (in.)	
Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Compliance	
Location RatingWetLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
Energy StarNoDLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
DLC ApprovedYesDLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
DLC IDS-RENY83B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
B.U.G. RatingB5-U3-G2Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	••	
Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
CA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	-	
California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		T20 Exempt - Fixtures Not
Title 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	California Status	
California Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
RoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
FCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	•	
SDS SheetLED_FixtureAdditional InformationPowder CoatedAdditional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount		
Additional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	•	
Additional InformationPowder CoatedSpecification NoteType V Light DistributionIncludes2-3/8 inch Slip-fitter Mount	Additional Information	
Specification Note Type V Light Distribution   Includes 2-3/8 inch Slip-fitter Mount		Powder Coated
Includes 2-3/8 inch Slip-fitter Mount		
· · · · ·	· ·	
	Warranty	5 Year Limited - Fixtures

