SATCO" NUVO"

Project Name

Location

Prepared By



NUVO 65-845-4

200W LED AREA LIGHT TYPE IV

Notes

www] 01-15-2024 02:40:07

StatusActiveTixture TypeArea LightTixture TypeArea LightPinshBronzeWattage200Wumen Output26536LCCT (Kelvin)5000KP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEDControl2000Specifications2000Control <td< th=""><th>General</th><th></th></td<>	General	
instruce TypeArea LightFinishBronzeWattage200WLumen Output26536LCCT (Kelvin)5000KFemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecifications80Coltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVNeight (b.)8.42WaterialDie-cast AluminumDimensions22.4ComplianceS-26CS3WSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WJ.J.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleLeadCalifornia StatusLawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalifornia InformationYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributionncudes2-3/8 inch Slip-fitter Mount	Status	Active
InishBronzeWattage200WLumen Output26536LCCT (Kelvin)5000KFemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecifications50000Specifications80Coltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptional_ens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVNeight (b.)8.42WaterialDie-cast AluminumDimensions22.4ComplianceSecosawSafety ListingCULus - Certified_ocation RatingWetEnergy StarNoDLC ApprovedYesDLC JDS-26CS3W3.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia StatusLeadCalifornia Prop 65LeadCompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributionncludes2-3/8 inch Slip-fitter Mount		
Internet26536LCCT (Kelvin)5000KFemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDCRI80/oltage120V-277VRated Hours50000Operating Temperature-40C (40F) to +45C (+113F)Opmining Note0-10V DimmablePhotocell or SensorOptionalColliderBuilt-in surge protection - 4KVNeight (lb.)8.42VaterialDie-cast AluminumDimensions22.4ComplianceVesSafety ListingcULus - CertifiedLocation RatingWetChaprovedYesCL ApprovedYesCL ApprovedYes <t< td=""><td>Finish</td><td></td></t<>	Finish	
Lumen Output26536LCCT (Kelvin)5000KTemperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDCRI80/oltage120V-277VRated Hours50000Operating Temperature40C (-40F) to +45C (+113F)OpmableYes-DimmableOptionalOptionalPolocell or SensorOptionalPolycarbonate (PC)Built-in surge protection - 4KVNeight (lb.)8.42MaterialDie-cast AluminumDimensions22.4ComplianceVesSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoOLC ApprovedYesDLC IDS-26CS3WB.UG. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in California Title 20 / 24 StatusCalifornia StatusLawful for sale in California RoHS CompliantCA T20 / T24 RationaleYesCSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distribution rupe IV Light Distribution rupe IV Light Distributionncludes2-3/8 inch Slip-fitter Mount	Wattage	200W
ControlControlFermperatureNatural LightP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsEEDFechnologyLEDCRI80/oltage120V-277VRated Hours50000Operating Temperature40C (40F) to +45C (+113F)DimmableYes-DimmablePhotocell or SensorOptionalPhotocell or SensorOptionalPolycarbonate (PC)Built-in surge protection - 4KVNeight (b.)8.42VaterialDie-cast AluminumDimensions14.4Length (in.)3.11Width (in.)14.4Length (in.)3.11Midth (in.)14.4Length (in.)S-26CS3WSafety ListingCULus - CertifiedLocation RatingWetPincey StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleRegulatedCalifornia StatusLawful for saleCalifornia Prop 65LeadCompliantYesCC CompliantYesCC CompliantYesCC CompliantYesCC CompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributionneudaes2-3/8 inch Slip-fitter Mount <td>Lumen Output</td> <td>26536L</td>	Lumen Output	26536L
P RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsIndoor; OutdoorSpecifications80CRI80/oltage120V-277VRated Hours50000Deparating Temperature40C (-40F) to +45C (+113F)Yes-DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42MaterialDie-cast AluminumDimensions14.4Length (in.)3.11Mdth (in.)14.4ComplianceSafety ListingCulLus - CertifiedVetSafety ListingCulLus - CertifiedJour StarNoDLC ApprovedYesDLC ApprovedYesDLC 1DS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadCompliantYesFCC CompliantYesSDS SheetLEDAdditional InformationPowder CoatedSpecification NoteT20 IV Light Distribution res/SDS SheetAdditional InformationPowder CoatedSpecification NoteT20/S inch Slip-fitter Mount	CCT (Kelvin)	5000K
Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsFechnologyLEDCRI80//oltage120V-277VRated Hours50000Deparating Temperature-40C (-40F) to +45C (+113F)DinmableYes-DinmableDinming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVNeight (lb.)8.42WaterialDie-cast AluminumDimensions14.4Length (in.)3.11Width (in.)14.4Length (in.)22.4ComplianceSafety ListingCulLus - CertifiedSelectionLocation RatingWetSafety ListingCULus - CertifiedLocation RatingWetDuc C ApprovedYesSDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distribution 2-3/8 inch Slip-fitter Mount	Temperature	Natural Light
SpecificationsSpecificationsFechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (-40F) to +45C (+113F)Yes-DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalens MaterialPolycarbonate (PC)Built-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions-teight (in.)3.11Mdth (in.)14.4energy StarNoComplianceSefety ListingCUL ApprovedYesDLC ApprovedYesDLC ApprovedYesDLC ApprovedYesCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoth ScoepliantYesCC CompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light DistributionSpecification NoteType IV Light DistributionRodicatedCalifornia StatusCompliantSpecification NoteSpecification NoteType IV Light DistributionRodication ReligitionCalifornia StatusCompliantYesCompliantSpecification NoteCompliantSpecification Note<	IP Rating	IP65
FechnologyLEDCRI80Voltage120V-277VRated Hours50000Operating Temperature40C (40F) to +45C (+113F)Yes-DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalPenotocell or SensorOptionalPenotocell or SensorOptionalPolycarbonate (PC)Built-in surge protection - 4KVSurge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions22.4Compliance22.4ComplianceSafety ListingCulLus - Certified0.0Location RatingWetSafety ListingCULus - CertifiedCocation RatingYesDuC ApprovedYesDuc J Z4 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadCalifornia Prop 65LeadCalifornia Prop 65LeadCalifornia InformationYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributionncludes2-3/8 inch Slip-fitter Mount	Indoor or Outdoor Fixture	Indoor; Outdoor
CRIBitCRI80Voltage120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalPhotocell or SensorOptionalBuilt-in surge protectionBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions	Specifications	
CRI80ZAIL120V-277VRated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalPhotocell or SensorOptionalSurge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42VlaterialDie-cast AluminumDimensions-14.4-ength (in.)3.11Midth (in.)14.4Length (in.)22.4Compliance	Technology	LED
Rated Hours50000Aated Hours50000Operating Temperature40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVNeight (lb.)8.42MaterialDie-cast AluminumDimensions3.11Height (in.)3.11Midth (in.)14.4Length (in.)22.4ComplianceVesSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadCompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributioncludes2-3/8 inch Slip-fitter Mount	CRI	80
Rated Hours50000Operating Temperature40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalPhotocell or SensorOptionalSurge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions3.11Midth (in.)3.11Midth (in.)14.4Length (in.)3.11Midth (in.)40C (-40F) to +45C (+113F)Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributioncludes2-3/8 inch Slip-fitter Mount		
DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions3.11Height (in.)3.11Midth (in.)14.4Length (in.)22.4ComplianceWetSafety ListingcULus - CertifiedLocation RatingWetDuc CapprovedYesDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in California Itle 20 / 24 StatusCalifornia Prop 65LeadCalifornia Prop 65LeadCalifornia InformationYesCompliantYesCompliantYesCompliantYesCalifornia InformationPowder CoatedSpecification NoteType IV Light Distribution 2-3/8 inch Slip-fitter Mount	Rated Hours	50000
DimmableYes-DimmableDimming Note0-10V DimmingPhotocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42WaterialDie-cast AluminumDimensions3.11Height (in.)3.11Midth (in.)14.4Length (in.)22.4ComplianceWetSafety ListingcULus - CertifiedLocation RatingWetDuc CapprovedYesDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in California Itle 20 / 24 StatusCalifornia Prop 65LeadCalifornia Prop 65LeadCalifornia InformationYesCompliantYesCompliantYesCompliantYesCalifornia InformationPowder CoatedSpecification NoteType IV Light Distribution 2-3/8 inch Slip-fitter Mount		
Photocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42MaterialDie-cast AluminumDimensions14.4Length (in.)3.11Width (in.)14.4Length (in.)22.4ComplianceVetSafety ListingcULus - CertifiedLocation RatingWetDuc ApprovedYesDLC IDS-26CS3WJ.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadCalifornia StatusLawful for saleCalifornia InformationYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributioncaludes2-3/8 inch Slip-fitter Mount	Dimmable	
Photocell or SensorOptionalLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42MaterialDie-cast AluminumDimensions14.4Length (in.)3.11Width (in.)14.4Length (in.)22.4ComplianceVetSafety ListingcULus - CertifiedLocation RatingWetDuc ApprovedYesDLC IDS-26CS3WJ.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadCalifornia StatusLawful for saleCalifornia InformationYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributioncaludes2-3/8 inch Slip-fitter Mount	Dimming Note	0-10V Dimming
Lens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 4KVWeight (lb.)8.42MaterialDie-cast AluminumDimensions3.11Height (in.)3.11Midth (in.)14.4Length (in.)22.4ComplianceULus - CertifiedSafety ListingCULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadCalifornia Prop 65LeadCOMPliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification Note2-3/8 inch Slip-fitter Mount	Photocell or Sensor	
Weight (lb.)8.42WaterialDie-cast AluminumDimensions3.11Midth (in.)14.4Leight (in.)22.4Compliance22.4Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleLawful for sale in CaliforniaFite 20 / 24 StatusLawful for saleCalifornia Prop 65LeadCOC CompliantYesCOC CompliantYesCA Gampa SheetLED_FixtureAdditional InformationPowder CoatedSpecification Note2-3/8 inch Slip-fitter Mount	Lens Material	· ·
Material Die-cast Aluminum Dimensions Height (in.) 3.11 Midth (in.) 14.4 Length (in.) 22.4 Compliance Safety Listing CULus - Certified Location Rating Wet Energy Star No DLC Approved Yes DLC Approved Yes DLC ID S-26CS3W B.U.G. Rating B4-U3-G4 Dark Sky Compliant No T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes SDS Sheet LED_Fixture Additional Information Powder Coated Specification Note Type IV Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	Surge Protection	Built-in surge protection - 4KV
DimensionsHeight (in.)3.11Midth (in.)14.4Length (in.)22.4ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification Note2-3/8 inch Slip-fitter Mount	Weight (lb.)	8.42
Height (in.)3.11Midth (in.)14.4Length (in.)22.4Compliance22.4Safety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCOMPS SheetYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributionncludes2-3/8 inch Slip-fitter Mount	Material	Die-cast Aluminum
Width (in.)14.4Length (in.)22.4ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distribution rulesncludes2-3/8 inch Slip-fitter Mount	Dimensions	
Width (in.)14.4Length (in.)22.4ComplianceSafety ListingcULus - CertifiedLocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3W3.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distribution ncludes2-3/8 inch Slip-fitter Mount	Height (in.)	3.11
ComplianceSafety ListingcULus - CertifiedJocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCC CompliantYesCC CompliantYesCA T20 / T24 RationaleLawful for saleCalifornia StatusLawful for saleCalifornia StatusLeadCalifornia Prop 65LeadCompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributionncludes2-3/8 inch Slip-fitter Mount	Width (in.)	14.4
Safety ListingcULus - CertifiedJocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCC CompliantYesCC CompliantYesCC CompliantYesCA T20 / T24 RationaleLawful for saleCalifornia StatusLawful for saleCalifornia StatusLeadCalifornia Prop 65LeadCompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributionncludes2-3/8 inch Slip-fitter Mount	Length (in.)	22.4
Safety ListingcULus - CertifiedJocation RatingWetEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCC CompliantYesCC CompliantYesCC CompliantYesCA T20 / T24 RationaleLawful for saleCalifornia StatusLawful for saleCalifornia StatusLeadCalifornia Prop 65LeadCompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributionncludes2-3/8 inch Slip-fitter Mount	Compliance	
Location RatingWetLocation RatingNoEnergy StarNoDLC ApprovedYesDLC IDS-26CS3W3.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalor CompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distribution 2-3/8 inch Slip-fitter Mount	-	cUL us - Certified
Energy StarNoEnergy StarNoDLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoDA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalifornia Prop 65LeadCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distribution 2-3/8 inch Slip-fitter Mount		
DLC ApprovedYesDLC IDS-26CS3WB.U.G. RatingB4-U3-G4Dark Sky CompliantNoDA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalifornia Prop 65LeadCC CompliantYesCC CompliantYesCDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification Note2-3/8 inch Slip-fitter Mount		
DLC IDS-26CS3W3.U.G. RatingB4-U3-G4Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalor CompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distribution 2-3/8 inch Slip-fitter Mount		
B.U.G. RatingB4-U3-G4Dark Sky CompliantNoDark Sky CompliantNoDA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedDalifornia StatusLawful for sale in CaliforniaDifle 20 / 24 StatusLawful for saleDalifornia Prop 65LeadCalifornia Prop 65LeadCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distribution a.3/8 inch Slip-fitter Mount	DLC ID	
Dark Sky CompliantNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCalifornia Prop 65LeadCC CompliantYesCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distribution 2-3/8 inch Slip-fitter Mount	B.U.G. Rating	
CA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationPowder CoatedSpecification NoteType IV Light Distributionncludes2-3/8 inch Slip-fitter Mount	-	
Fitle 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Powder Coated Specification Note Type IV Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	CA T20 / T24 Rationale	T20 Exempt - Fixtures Not
California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Powder Coated Specification Note Type IV Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	California Status	
RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Powder Coated Additional Information Type IV Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	Title 20 / 24 Status	Lawful for sale
RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Powder Coated Specification Note Type IV Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	California Prop 65	Lead
SDS Sheet LED_Fixture Additional Information Additional Information Additional Information Powder Coated Specification Note Type IV Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	RoHS Compliant	Yes
Additional Information Additional Information Additional Information Powder Coated Specification Note Type IV Light Distribution ncludes	FCC Compliant	Yes
Additional InformationPowder CoatedSpecification NoteType IV Light Distributionncludes2-3/8 inch Slip-fitter Mount	SDS Sheet	LED_Fixture
Specification Note Type IV Light Distribution ncludes 2-3/8 inch Slip-fitter Mount	Additional Information	
ncludes 2-3/8 inch Slip-fitter Mount	Additional Information	Powder Coated
	Specification Note	Type IV Light Distribution
Narranty 5 Year Limited - Fixtures	Includes	2-3/8 inch Slip-fitter Mount
	Warranty	5 Year Limited - Fixtures

