

PRODUCT INFORMATION

LED vapor tight fixtures

Efficiency and safety in one package

Applications

- Moisture-prone areas
- Cold storage/freezers
- Warehouses
- Food processing
- Parking structures
- Generally harsh environments

Features

- Available with or without occupancy sensor
- Tamper/vandal resistant
- High lumens/watt
- Heat resistant
- 100-277 range voltage
- 0-10V dimming
- Damp location
- CRI 80
- Available in 4000K and 5000K
- 50,000 hour life
- DLC certified
- 5 Year warranty



LED Vapor Tight Fixtures



Item Number	Lamp Description	Watt	Lumens	CCT	IP	CRI	Lumen P/W	Dimming	Voltage	Life/Hrs.	Certificate
62/1061	29W Vapor Proof Surface Mount – 4000K	29	3200	4000	IP65	80	112	0-10V	100-277V	50K	DLC 4.1
62/1062	29W Vapor Proof Surface Mount – 5000K	29	3400	5000	IP65	80	118	0-10V	100-277V	50K	DLC 4.1
62/1063	58W Vapor Proof Surface Mount – 4000K	58	6400	4000	IP65	80	110	0-10V	100-277V	50K	DLC 4.1
62/1064	58W Vapor Proof Surface Mount – 5000K	58	7000	5000	IP65	80	120	0-10V	100-277V	50K	DLC 4.1
62/1065	29W Vapor Proof Surface Mount – 4000K – w/OCC Sensor	29	3200	4000	IP65	80	112	0-10V	100-277V	50K	DLC 4.1
62/1066	29W Vapor Proof Surface Mount – 5000K – w/OCC Sensor	29	3400	5000	IP65	80	118	0-10V	100-277V	50K	DLC 4.1
62/1067	58W Vapor Proof Surface Mount – 4000K – w/OCC Sensor	58	6400	4000	IP65	80	110	0-10V	100-277V	50K	DLC 4.1
62/1068	58W Vapor Proof Surface Mount – 5000K – w/OCC Sensor	58	7000	5000	IP65	80	120	0-10V	100-277V	50K	DLC 4.1